

Package: roxytest (via r-universe)

October 13, 2026

Type Package

Title Various Tests with 'roxygen2'

Version 0.0.2

Maintainer Mikkel Meyer Andersen <mikl@math.aau.dk>

Description Various tests as 'roxygen2' roclets: e.g. 'testthat' and 'tinytest' tests. Also other static analysis tools as checking parameter documentation consistency and others.

License GPL (>= 2)

Imports roxygen2, methods

Depends R (>= 2.10)

Suggests testthat (>= 2.1.0), tinytest (>= 1.1.0), knitr, rmarkdown

BugReports <https://github.com/mikldk/roxytest/issues>

Encoding UTF-8

Roxygen list(markdown = TRUE, roclets = c("`rd", "`collate",
`namespace"))

RoxygenNote 7.2.3

VignetteBuilder knitr

Config/pak/sysreqs cmake make libuv1-dev libxml2-dev

Repository <https://mikldk.r-universe.dev>

Date/Publication 2023-01-12 07:18:25 UTC

RemoteUrl <https://github.com/mikldk/roxytest>

RemoteRef HEAD

RemoteSha a54646c7a36d2726bd79ac39a7fbb6e06b4b95a8

Contents

examples_roclet	2
param_roclet	3
return_roclet	3

roxy_tag_parse.roxy_tag_testexamples	4
roxy_tag_parse.roxy_tag_tests	5
testthat_roclet	5
tinytest_roclet	6
Index	7

examples_roclet	<i>Roclet: check presence of @examples in documentation for exported functions</i>
-----------------	--

Description

This roclet checks presence of @example/@examples.

Generally you will not call this function directly but will instead use `roxygen2::roxygenise()` specifying this roclet.

Usage

```
examples_roclet()
```

Value

A roclet to be used e.g. with `roxygen2::roxygenise()`

See Also

Other roclets: `testthat_roclet`, `tinytest_roclet`, `param_roclet`, `return_roclet`, `namespace_roclet`, `rd_roclet`, `vignette_roclet`.

Other roclets: `param_roclet()`, `return_roclet()`, `testthat_roclet()`, `tinytest_roclet()`

Examples

```
x <- "' Summing two numbers\n#'\n#' @export\nf <- function(x, y) {\n  x + y\n}\n"
cat(x)
roxygen2::roc_proc_text(examples_roclet(), x)
```

param_roclet

Roclet: check consistency of param documentation

Description

This roclet checks consistency between function arguments and the documentation. The idea is to catch such errors earlier than in an R CMD check.

Generally you will not call this function directly but will instead use `roxygen2::roxygenise()` specifying this roclet.

Usage

```
param_roclet()
```

Value

A roclet to be used e.g. with `roxygen2::roxygenise()`

See Also

Other roclets: `testthat_roclet`, `tinytest_roclet`, `examples_roclet`, `return_roclet`, `namespace_roclet`, `rd_roclet`, `vignette_roclet`.

Other roclets: `examples_roclet()`, `return_roclet()`, `testthat_roclet()`, `tinytest_roclet()`

Examples

```
x <- "' Summing two numbers\n#'\n#' @export\nf <- function(x, y) {\n  x + y\n}\n"
cat(x)
roxygen2::roc_proc_text(param_roclet(), x)
```

return_roclet

Roclet: check presence of @return in documentation for exported functions

Description

This roclet checks presence of @return that generates \value in Rd files.

Generally you will not call this function directly but will instead use `roxygen2::roxygenise()` specifying this roclet.

Usage

```
return_roclet()
```

Value

A roclet to be used e.g. with `roxygen2::roxygenise()`

See Also

Other roclets: `testthat_roclet`, `tinytest_roclet`, `param_roclet`, `examples_roclet`, `namespace_roclet`, `rd_roclet`, `vignette_roclet`.

Other roclets: `examples_roclet()`, `param_roclet()`, `testthat_roclet()`, `tinytest_roclet()`

Examples

```
x <- "' Summing two numbers\n#'\n#' @export\nf <- function(x, y) {\n  x + y\n}\n"
cat(x)
roxygen2::roc_proc_text(return_roclet(), x)
```

`roxy_tag_parse.roxy_tag_testexamples`*Parse testexamples tag*

Description

Parse testexamples tag

Usage

```
## S3 method for class 'roxy_tag_testexamples'
roxy_tag_parse(x)
```

Arguments

x	Input
---	-------

Value

Parsed tag

```
roxy_tag_parse.roxy_tag_tests
```

Parse tests tag

Description

Parse tests tag

Usage

```
## S3 method for class 'roxy_tag_tests'
roxy_tag_parse(x)
```

Arguments

x Input

Value

Parsed tag

```
testthat_roclet              Roclet: make testthat test-files.
```

Description

This roclet is a workhorse of roxytest, producing the testthat test files specified.

Generally you will not call this function directly but will instead use `roxygen2::roxygenise()` specifying this roclet.

Usage

```
testthat_roclet()
```

Value

A roclet to be used e.g. with `roxygen2::roxygenise()`

See Also

Other roclets: `param_roclet`, `examples_roclet`, `return_roclet`, `tinytest_roclet`, `namespace_roclet`, `rd_roclet`, `vignette_roclet`.

Other roclets: `examples_roclet()`, `param_roclet()`, `return_roclet()`, `tinytest_roclet()`

Examples

```
x <- "' @tests\n#' expect_equal(2, 2)\nNULL\n"
cat(x)
o <- roxygen2::roc_proc_text(testthat_roclet(), x)
cat(o$tests[[1]])
```

tinytest_roclet	<i>Roclet: make tinytest test-files.</i>
-----------------	--

Description

This roclet is a workhorse of roxytest, producing the tinytest test files specified.

Generally you will not call this function directly but will instead use [roxygen2::roxygenise\(\)](#) specifying this roclet.

Usage

```
tinytest_roclet()
```

Value

A roclet to be used e.g. with [roxygen2::roxygenise\(\)](#)

See Also

Other roclets: [param_roclet](#), [examples_roclet](#), [return_roclet](#), [testthat_roclet](#), [namespace_roclet](#), [rd_roclet](#), [vignette_roclet](#).

Other roclets: [examples_roclet\(\)](#), [param_roclet\(\)](#), [return_roclet\(\)](#), [testthat_roclet\(\)](#)

Examples

```
x <- "' @tests\n#' expect_equal(2, 2)\nNULL\n"
cat(x)
o <- roxygen2::roc_proc_text(tinytest_roclet(), x)
cat(o$tests[[1]])
```

Index

* roclets

- examples_roclet, [2](#)
- param_roclet, [3](#)
- return_roclet, [3](#)
- testthat_roclet, [5](#)
- tinytest_roclet, [6](#)

examples_roclet, [2](#), [3–6](#)

namespace_roclet, [2–6](#)

param_roclet, [2](#), [3](#), [4–6](#)

rd_roclet, [2–6](#)

return_roclet, [2](#), [3](#), [3](#), [5](#), [6](#)

roxy_tag_parse.roxy_tag_testexamples,
[4](#)

roxy_tag_parse.roxy_tag_tests, [5](#)

roxygen2::roxygenise(), [2–6](#)

testthat_roclet, [2–4](#), [5](#), [6](#)

tinytest_roclet, [2–5](#), [6](#)

vignette_roclet, [2–6](#)